



## 71 1303

# Open Gear Synthetic Non-Melting Grease

### CHARACTERISTICS:

- Synthesized superior-quality grease, blended specifically to be extremely adhesive, non drip and none melting.
- Contains special organ-metallic anti-seizing and anti-wear agents.
- It has been designed specifically for use on open gears, cams, etc. It will not drip or sling off.

### PHYSICAL PROPERTIES

TESTS	71 1303		
	71 1303 /1.5	71 1303 /2	71 1303 /3
N.L.G.I. Grade	1.5	2	3
Penetration	285	270	240
Penetration after 60 strokes	287	270	240
Penetration after 60 strokes	302	278	245
Penetration with 10% water after 60 strokes	306	285	250
Dripping Point en °C	None	None	None
Melting Point	None	None	None
Corrosion – Copper Strip Test @ 163°C-3 hrs.	Negative	Negative	Negative
Timken Load	45 Kgs (100) lbs	45 Kgs (100) lbs	45 Kgs (100) lbs
Oil Separation %	< 3%	< 3%	< 3%
Viscosity of Base Oil cSt @ 40°C	320	560	1000
Additive	Metal-Organic	Metal-Organic	Metal-Organic
Maximum temperature en °C	350	350	355
Minimum temperature en °C	-25	-17	-0

---

### **Xp Lab, Inc.**

946 W. HAWTHORN ST. SAN DIEGO, CA 92101

TEL. (619) 233-3111 FAX: (619)233-3112

[Xp3@xplab.com](mailto:Xp3@xplab.com)

<http://www.xplab.com>