



72 1113

High Performance Synthetic Grease For Industrial Equipment

CHARACTERISTICS:

- A synthetic hybrid calcium sulfonate / inorganic soap grease.
- Demonstrates exceptional mechanical stability
- Resistance to continuous both high and extreme low temperatures -30 to + 260 °C.
- Fully formulated with the latest in EP additive technology
- Functions very well under high loads.
- Unique thickening structure
- Virtually eliminates water washout,
- Resists oxidation and inhibits corrosion.

TYPICAL APPLICATIONS:

- Bearings exposed to high temperatures
- Bearings exposed to water (such as wet end of paper machine)
- Calendar rolls
- Heavy machinery
- Gear boxes requiring greases
- Roller bearings
- Industrial equipment in an adverse environment or under heavy load
- Bearing operating at low or high rpm
- Electric motors
- Rotary joints
- Crusher Bearings
- Fifth Wheel

Xp Lab, Inc.

946 W. HAWTHORN ST. SAN DIEGO, CA 92101
TEL. (619) 233-3111 FAX: (619)233-3112
Xp3@xplab.com <http://www.xplab.com>



PHYSICAL PROPERTIES:

Test	ASTM	72 1113
NLGI Grade		2
Penetration @ 25°C, 60 strokes		275
Dropping Point, °C		300
Oil separation, 24 hours @ 25°C		0.1%
Oxidation Stability	D-942	
@ 100 hrs.		0 PSI
@ 500 hrs.		2 PSI
@ 1,000 hrs.		9 PSI
Roll stability penetration	D-1831	+19
4 ball wear test, m/m scar (75°C, 40 kg, 1200 rpm, 1h))	D-2266	0.39
4 ball EP test, LWI, kg	D-2596	500
Timken OK load, Kg (lbs)	D-2509	27 (65)
Rust test rating	D-1743	1,1,1
Water washout @ 79°C % loss	D-1264	2.5%
Viscosity cSt @ 40°C		226
Viscosity cSt @ 100°C		25.5
Operating temperature range °C		-26 hasta + 265
Additives		EP, AW, AOX

Xp Lab, Inc.

946 W. HAWTHORN ST. SAN DIEGO, CA 92101

TEL. (619) 233-3111 FAX: (619)233-3112

Xp3@xplab.com

<http://www.xplab.com>