



79 6201

PAG Synthetic Gear Oils

CHARACTERISTICS:

- 100% Polyalkalene Glycol based gear oil
- Offers a higher performance at a full temperature range as well as under severe environmental conditions.
- Energy conservation due to the reduction of friction.
- Reduced gasket wear.
- Reduced oil consumption.
- Longer periods between maintenance.
- Stable viscosity at high temperatures.

TYPICAL SPECIFICATIONS:

79-6201	/032	/046	/068	/150	/159	/220	/460	/680	/689
ISO Grade	32	46	68	150	1500	220	460	680	680
Viscosity cSt @ 40°C	35	47	59	143	1150	237	475	615	533
Viscosity cSt @ 40°C	6.7	8.8	10.8	21.9	185	38.2	77	85.9	83
Viscosity Index	160	170	174	180	287	212	248	235	235
Pour Point °C	-43	-40	-40	-29	-26	-26	-20	-27	-36
Flash Point °C	188	200	218	221	>260	221	238	282	260
FIRE Point °C	249	254	277	293	-	293	293	-	-
% Water	<0.25	<0.25	<0.25	<0.25	<0.25	<0.25	<0.25	<0.25	<0.25
Specific Gravity	0.989	0.992	0.995	1.002	1.058	1.004	1.004	1.010	1.010
Foam @ 24°C	0	0	0	0	0	0	0	0	0
Foam @ 93°C	0	0	0	0	0	0	0	0	0

Xp Lab, Inc.

946 W. HAWTHORN ST. SAN DIEGO, CA 92101

TEL. (619) 233-3111 FAX: (619)233-3112

Xp3@xplab.com

<http://www.xplab.com>